PLATINUM
ORLEN OIL

PRODUKTOVÝ **KATALOG**

OLEJE PRO OSOBNÍ AUTOMOBILY

Produkt	Kvalita	Viskozita	Atest	Splňuje kritéria	Ekvivalent MOGUL
PLATINUM PRO LL 0W-20	ACEA: C5	SAE: 0W-20	VW Standard 508 00; VW Standard 509 00;	-	-
PLATINUM PRO 0W-20	API: SN RC ILSAC: GF-5	SAE: 0W-20	-	-	MOGUL 0W-20 EXTREME LF IV
PLATINUM PRO New 0W-30	ACEA: A5/B5	SAE: 0W-30	-	VW 503 00, 506 00, 506 01;	MOGUL 0W-30 EXTREME LFII
PLATINUM PRO 0W-40	API: SN ACEA: A3/B4	SAE: 0W-40	-	Mercedes-Benz 229.3 / 229.5 / 226.5; VW 502 00 / 505 00; Porsche A40; Ford WSS-M2C937-A; Renault RN0700/0710;	MOGUL 0W-40 EXTREME
PLATINUM PRO F 5W-30	API: SL/CF ACEA: A1/B1 ACEA: A5/B5	SAE: 5W-30	Ford WSS-M2C913-C; Ford WSS-M2C913-D;	Renault RN 0700; Jaguar JTJLR 03.5003;	-
PLATINUM PRO V 5W-30	API: SN ACEA: C3	SAE: 5W-30	VW Standard 504 00; VW Standard 507 00; MB-Approval 229.51; BMW Longlife-04; Porsche C30;	-	-
PLATINUM PRO XD 5W-30	API: SN ACEA: C3, C2	SAE: 5W-30	MB-Approval 229.52; BMW Longlife-04;	Mercedes-Benz 229.31 / 229.51; Opel/General Motors GM Dexos 2; VW 505 01 / 505 00;	-
PLATINUM PRO XFI 5W-30	API: SN/SM/CF ACEA: C2	SAE: 5W-30	Renault 0700;	PSA B71 2290 / Citroen, Peugeot, Fiat 9.55535-S1;	-
PLATINUM PRO XJ 5W-30	ACEA: C2 JASO DL-1	SAE: 5W-30	-	-	-
PLATINUM PRO C3 5W-40	API: SN/SM/CF ACEA: C3	SAE: 5W-40	VW Standard 505 00, 505 01; MB-Approval 229.31; MB-Approval 226.5; Renault RN0700/0710;	Porsche A40; Ford WSS-M2C917A; BMW Longlife-04;	MOGUL 5W-40 EXTREME PD M MOGUL RACING 5W-40 X PD
PLATINUM PRO C4 5W-30	ACEA: C4	SAE: 5W-30	Renault RN0720; MB-Approval 226.51;	-	-

OLEJE PRO OSOBNÍ AUTOMOBILY

Produkt	Kvalita	Viskozita	Atest	Splňuje kritéria	Ekvivalent MOGUL
PLATINUM MaxExpert FR 0W-30	ACEA: C2	SAE: 0W-30	PSA PEUGEOT CITROËN B71 2312;	ORLEN OIL doporučuje: Fiat 9.55535-DS1; Fiat 9.55535-GS1;	-
PLATINUM MaxExpert 0W-30	API: SL ACEA: A5/B5	SAE: 0W-30	Volvo 95200377;	-	-
PLATINUM MaxExpert C5 5W-20	API: SN/SN-RC/CF ACEA: C5 ILSAC GF-5	SAE: 5W-20	FORD WSS-M2C948-B;	JLR 03.5004;	-
PLATINUM MaxExpert DEX1 5W-30	API: SN Plus, API: SN RC (Resource Conserving) ILSAC GF-5	SAE: 5W-30	-	GM dexos1™ Gen 2; Chrysler MS6395; Ford WSS-M2C946-A, WSS-M2C946-B1;	-
PLATINUM MaxExpert F 5W-30	API: SL/CF ACEA: A1/B1, A5/B5	SAE: 5W-30	Ford WSS-M2C913-C;	Ford WSS-M2C913-D; Renault RN 0700; Jaguar JTJLR 03.5003;	MOGUL 5W-30 EXTREME F MOGUL RACING 5W-30 F MOGUL 5W-30 PROFESSIONAL F
PLATINUM MaxExpert XF 5W-30	API: SM/CF ACEA: C2	SAE: 5W-30	Renault RN0700;	PSA B712290, B712288/ Citroen, Peugeot;	MOGUL 5W-30 PROFESSIONAL P
PLATINUM MaxExpert V 5W-30	API: SN ACEA: C3	SAE: 5W-30	VW Standard 504 00; VW Standard 507 00;	Mercedes-Benz 229.51; BMW Longlife-04; Porsche C30; Audi, Skoda, Seat;	MOGUL RACING 5W-30 MOGUL 5W-30 EXTREME LFIII MOGUL SPEED 5W-30
PLATINUM MaxExpert XD 5W-30	API: SN ACEA: C3, C2	SAE: 5W-30	MB-Approval 229.52;	Mercedes-Benz 229.31 / 229.51; BMW Longlife-04; Opel/General Motors GM Dexos 2; VW 505 01 / 505 00;	MOGUL 5W-30 PROFESSIONAL LFIII
PLATINUM MaxExpert C4 5W-30	ACEA: C4	SAE: 5W-30	-	Renault RN0720; Mercedes-Benz 226.51;	MOGUL 5W-30 C4 MOGUL 5W-30 PROFESSIONAL R
PLATINUM MaxExpert C3 5W-40	API: SN/SM/CF ACEA: C3	SAE: 5W-40	MB-Approval 229.31; VW Standard 505 00; VW Standard 505 01;	Mercedes-Benz 226.5; Renault RN0700/0710; Porsche A40; Ford WSS-M2C917A; General Motors GM Dexos 2;	MOGUL 5W-40 EXTREME PD
PLATINUM MaxExpert A3/B4 10W-40	API: SN/SM/CF ACEA: A3/B4	SAE: 10W-40	-	VW 502 00/505 00; Mercedes-Benz 229.1 Renault RN 0700, RN0710; Fiat 9.55535 D2; Fiat 9.55535 G2;	MOGUL 10W-40 EXTREME MOGUL 10W-40 PROFESSIONAL

NOVINKA

PLATINUM MaxExpert A3/B4 5W-30	API: SL ACEA: A3/B4	SAE: 5W-30	MB-Approval 229.3; VW Standard 502 00; VW Standard 505 00;	-	-

OLEJE PRO OSOBNÍ AUTOMOBILY

Produkt	Kvalita	Viskozita	Splňuje kritéria	Ekvivalent MOGUL
PLATINUM Classic GAS SYNTHETIC 5W-40	API: SL	SAE: 5W-40	-	-
PLATINUM Classic GAS SEMISYNTHETIC 10W-40	API: SL	SAE: 10W-40	-	-
PLATINUM Classic GAS MINERAL 15W-40	API: SL	SAE: 15W-40	-	-
PLATINUM Classic SYNTHETIC 5W-40	API: SL/SJ/CF ACEA: A3/B3	SAE: 5W-40	Mercedes – Benz 229.1;	-
PLATINUM Classic SEMISYNTHETIC 10W-40	API: SL/SJ/CF ACEA: A3/B3	SAE: 10W-40	Mercedes – Benz 229.1;	-
PLATINUM Classic MINERAL 15W-40	API: SL/SJ/CF ACEA: A3/ B3	SAE: 15W-40	Mercedes – Benz 229.1;	-
PLATINUM Classic DIESEL SYNTHETIC 5W-40	API: CF	SAE: 5W-40	Mercedes – Benz 229.1;	-
PLATINUM Classic DIESEL SEMISYNTHETIC 10W-40	API: CF	SAE:10W-40	Mercedes – Benz 229.1;	-
PLATINUM Classic DIESEL MINERAL 15W-40	API: CF	SAE: 15W-40	Mercedes – Benz 229.1;	-
PLATINUM Classic LIFE+ 20W-50	API: SG/CF-4	SAE: 20W-50	-	MOGUL M7ADS III 20W-50
PLATINUM Classic SYNTHETIC RACING 5W-40	API: SM/CF ACEA: A3/B4	SAE: 5W-40	VW 502.00/505.00; Mercedes-Benz 229.3; BMW LL-01, GM-LL-B-025; Porsche A40; Renault RN 710/700;	MOGUL RACING 5W-40 MOGUL SPEED 5W-40
PLATINUM Classic SEMISYNTHETIC PLUS 10W-40	API: SL/CF ACEA: A3/B3, A3/B4	SAE: 10W-40	Mercedes-Benz 229.1; VW 501 01/ 505 00;	MOGUL GX-FE MOGUL SPEED 10W-40
PLATINUM Classic SEMISYNTHETIC BASIC 10W-40	API: SL/CF	SAE: 10W-40	-	MOGUL 10W-40
PLATINUM Classic MINERAL EXTREME 15W-40	API: SL/CF ACEA: A3/ B3	SAE: 15W-40	Mercedes-Benz 229.1; VW 501 01/ 505 00;	MOGUL GX FELICIA MOGUL 15W-40 EXTREME

OLEJE PRO MOTORKY

Produkt	Kvalita	Viskozita	Ekvivalent MOGUL
PLATINUM RIDER 4T 10W-40	API: SN/SM JASO MA/MA-2	SAE: 10W-40	MOGUL MOTO 4T 10W-40
PLATINUM RIDER CRUISER 4T 15W-50	API: SL JASO MA-2	SAE: 15W-50	-
PLATINUM RIDER RACING 4T 5W-40	API: SN/SM JASO MA/MA-2	SAE: 5W-40	MOGUL MOTO 4T 5W-40
PLATINUM RIDER SCOOTER 4T	API: SL JASO MA-2	SAE: 5W-40	-
PLATINUM RIDER V-TWIN 4T 20W-50	API: SJ JASO MA-2	SAE: 20W-50	MOGUL MOTO 4T 20W-50
PLATINUM RIDER SCOOTER 2T	API: TC JASO FD ISO-L-EGD	-	MOGUL ALFA 2T
PLATINUM RIDER RACING 2T	API: TC JASO FD ISO-L-EGD	-	MOGUL TSF
PLATINUM RIDER 2T	API: TB	SAE: 40	MOGUL 2T

MOTOROVÉ A PŘEVODOVÉ OLEJE

Produkt	Kvalita	Viskozita	Splňuje kritéria	Ekvivalent MOGUL
ORLEN OIL STANDARD CE/SG 15W-40	API: CE/SG	SAE: 15W-40	-	MOGUL M7ADS III 15W-40
ORLEN OIL UNIWERSALNY SF/CC 15W-40	API: CF/CC	SAE: 15W-40	-	MOGUL SUPER STABIL 15W-40 MOGUL SPEED 15W-40
ORLEN OIL M6AD SC/CB SAE 30	API: SC/CB	SAE: 30	-	MOGUL M6AD SAE30
ORLEN OIL M6AD SAE 40	API: SC/CB	SAE: 40	-	MOGUL M6AD
ORLEN OIL M6ADSII	API: CE/CF-4	SAE: 30	-	MOGUL M6ADS II PLUS
ORLEN OIL M7ADSIII 20W-40	API: SG/CF-4	SAE 20W-40	-	MOGUL M7ADS III 20W-40
ORLEN OIL M7ADSIIIPLUS SG/CF-4 15W/40	API: SG/CF-4	SAE 15W-40	-	-
ORLEN OIL M8AD	API: SE/CB	SAE 15W-50	-	MOGUL SUPER 15W-50
ORLEN OIL LUBRO SF/CC 20W-50	API: CF/CC	SAE 20W-50	-	-
ORLEN OIL SELEKTOL SPEC. SD 20W-40	API: SD	SAE 20W-40	-	-
ORLEN OIL LUX-10	API: SA	SAE: 30	-	-
ORLEN OIL 2T SEMISYNT. TC (C)	API: TC	-	-	-
ORLEN OIL MIXOL S	API: TB/TA	-	PN-70/C-96092	-

OLEJE PRO NÁKLADNÍ AUTOMOBILY, AUTOBUSY A TĚŽKÁ ZAŘÍZENÍ

PLATINUM ULTOR

Produkt	Kvalita	Viskozita	Atest	Splňuje kritéria	Ekvivalent MOGUL
PLATINUM ULTOR Fuel Economy 5W-30	API: FA-4/SN	SAE: 5W-30	MB-Approval 228.61;	JASO DH-1; CUMMINS CES 20087; DETROIT DIESEL DDC 93K223;	-
PLATINUM ULTOR Perfect 5W-30	API: SN/CK-4/CJ-4 ACEA: E6, E7, E9	SAE: 5W-30	MB-Approval 228.51; Volvo VDS-4.5; Mack EO-S-4.5; RENAULT VI RLD-3; MAN M3677; Meet Scania LA specification;	CUMMINS CES 20086; DAIMLER MB 228.31, MB 228.52; Detroit Diesel Extranet 93K222; DEUTZ DQC IV-18 LA; MTU TYPE 3.1; Volvo VDS-3; Scania LDF-4; MAN M3271-1; M3775, M3477; Caterpillar ECF-3; DAF; IVECO; FORD WSS-M2C213-A;	MOGUL DIESEL L-SAPS 5W-30
PLATINUM ULTOR Scandiv 10W-40	API: CF ACEA: E4,E7	SAE: 10W-40	Meet Scania LDF-3 specification;	Scania LDF-2; Mercedes-Benz 228.5; MAN M3277; Deutz DQC III-10; Volvo VDS-3; Renault RVI RLD-2; Mack EO-N; MTU Type 3; DAF Extended Drain;	-
PLATINUM ULTOR Complete 10W-40	API: CI-4/CJ-4/CK-4, SN ACEA: E6, E7, E9	SAE: 10W-40	MB-Approval 228.51; Volvo VDS-4; Renault RVI RLD-3; Mack EO-O Premium Plus; Deutz DQC IV-10 LA; MTU Type 3.1; This product meets Cummins® Eng. Std. 20081;	MAN M3477; Caterpillar ECF-3; DDC 93K218; JASO DH-2;	-
PLATINUM ULTOR Maximo 5W-30	ACEA: E4	SAE: 5W-30	MB-Approval 228.5; Volvo VDS-3; Mack EO-N; Renault VI RLD-2;	MAN M3277; MTU Type 3; Renault RVI RXD, RLD; Scania LDF-3; Cummins CES 20077; Deutz DQC IV-18; Voith Class A;	MOGUL DIESEL ULTRA
PLATINUM ULTOR Max 5W-40		SAE: 5W-40			-
PLATINUM ULTOR Progress 10W-40	API: CI-4 ACEA: E6, E7, E9	SAE: 10W-40	MAN M3477; MB-Approval 228.51; Volvo VDS-3; Renault RVI RLD-2; Mack EO-N; MTU Type 3.1; Deutz DQC-IV-18 LA; This product meets Cummins Eng. Std. CES20076/77;	MAN 3271-1, DAF; JASO DH-2; Caterpillar ECF 1a; Deutz DQC TTCD; Renault RXD/RGD; MAZ;	MOGUL DIESEL L-SAPS 10W-40 MOGUL DIESEL CNG
PLATINUM ULTOR Optimo 10W-30	API: CK-4/CJ-4 ACEA: E9	SAE: 10W-30	Volvo VDS-4.5; Renault RVI RLD-3; Mack EO-O-S 4.5; Deutz DQC III-18 LA; MTU Type 2.1; MB-Approval 228.31; This product meets Cummins® Eng. Std. 20086;	MAN M3775, M3575; Caterpillar ECF-3; Detroit Diesel DFS 93K222; Ford WSS-M2C171-F1;	MOGUL DIESEL L-SAPS 10W-30
PLATINUM ULTOR Extreme 10W-40	API: CI-4/CH-4/CG-4 ACEA: E7, E4	SAE: 10W-40	MAN M3277; MB-Approval 228.5; Volvo VDS-3; Mack EO-N; Renault VI RLD-2;	DEUTZ DQC-III-10; MTU Type 2; MTU Type 3; MAN 3275; Jaso DH-1; Global DHD-1; DDC 93K215; Allison C-4;	MOGUL OPTIMAL MOGUL DIESEL DTT PLUS
PLATINUM ULTOR Master 10W-40	API: CH-4/CG-4 ACEA: E7, E4	SAE: 10W-40	-	Mercedes-Benz 228.5; MAN M 3275; Volvo VDS-2; Renault VI RLD;	MOGUL DIESEL DTT PLUS M
PLATINUM ULTOR Futuro 15W-40	API: CK-4/SN ACEA: E9, E7	SAE: 15W-40	MB-Approval 228.31, Volvo VDS-4.5 Renault RVI RLD-3, Mack EO-S 4.5 Deutz DQC III- 18LA This product meets Cummins Eng. Std. CES20086	MAN M 3775, MAN M 3575, MTU Type 2.1 Caterpillar ECF-3, Detroit Diesel 93K222 Ford WSS-M2C171-F1 Allison TES 439 JASO DH-2 MAZ	MOGUL DIESEL L-SAPS 15W-40

OLEJE PRO NÁKLADNÍ AUTOMOBILY, AUTOBUSY A TĚŽKÁ ZAŘÍZENÍ

Produkt	Kvalita	Viskozita	Atest	Splňuje kritéria	Ekvivalent MOGUL
PLATINUM ULTOR Plus 15W-40	API: CI-4/CH-4/CG-4, SL/SJ ACEA: E7, E5, E3	SAE: 15W-40	MB-Approval 228.3, Volvo VDS-3, MACK EO-N, EOM Plus, RENAULT RLD/RLD-2, This product meets Cummins® Eng.Std. CES20078, MTU TYPE 2, DEUTZ DQC-III-10.	CUMMINS CES 20076/77, DAF, IVECO, DDC 93K215,MAN M3275-1, Scania, CATERPILLAR ECF-2, ECF-1a,TEDOM 258-3, AVIA - TYP SILNIKA: 712, D407, D421.76, D421.85.	MOGUL DIESEL DTT EXTRA MOGUL TOP TIR MOGUL DIESEL DTT EXTRA M
PLATINUM ULTOR CH-4 15W-40	API: CH-4/CG-4/SL ACEA: E7, E5, E3	SAE: 15W-40	MB-Approval 228.3, Volvo VDS-3, MACK EO-N/ EOM Plus, RENAULT RLD/RLD-2, DEUTZ DQC-III-10, MTU TYPE 2.	MAN M3275-1, CUMMINS CES 20076/77/78, DAF, IVECO,DDC 93K215, Scania, CATERPILLAR ECF-2, ECF-1a,TATRA TDS 30/12, TEDOM 258-3, AVIA - TYP SILNIKA:712, D407, D421.76, D421.85.	-
PLATINUM ULTOR CG-4 15W-40	API: CG-4/SJ ACEA: E7	SAE: 15W-40	-	Mercedes-Benz 228.1; Volvo VDS-2; MACK EO-N; RENAULT RLD-2; DEUTZ DQC-II-10; MTU TYPE 1; TEDOM 258-3; DAF; CATERPILLAR ECF-1a; AVIA - TYP SILNIKA: 712, D407, D421.76, D421.85;	MOGUL DIESEL DTT P MOGUL DIESEL DTT
PLATINUM ULTOR Diesel 15W-40	API: CG-4/CF-4/CF ACEA: E2	SAE: 15W-40	-	Mercedes-Benz 228.1; MAN 271; Deutz DQC II-10; Volvo VDS;	-
PLATINUM ULTOR Diesel 15W-50	API: CG-4/CF-4/CF	SAE: 15W-50	-	Mercedes-Benz 228.1; MAN 271; MTU Type 1; Deutz DQC I-02;	-
PLATINUM ULTOR Diesel 20W-50	API: CG-4/CF-4/CF ACEA: E2	SAE: 20W-50	-	Mercedes-Benz 228.1; MAN 271; MTU Type 1; Deutz DQC I-02;	-
PLATINUM ULTOR Diesel L-SAPS 10W-40 M	API: CI-4 CEA: E7, E6	SAE: 10W-40	-	MAN M3477; Mercedes-Benz 228.51; VOLVO VDS-3; RENAULT RLD-2; Mack EO-N; MTU Type 3.1; DEUTZ DQC-III-10 LA; Cummins CES 20076/77; DAF;	MOGUL DIESEL L-SAPS 10W-40 M

OLEJE PRO ZEMĚDĚLSKÉ STROJE

PLATINUM AGRO

Produkt	Kvalita	Viskozita	Atest	Splňuje kritéria	Ekvivalent MOGUL
PLATINUM AGRO Supreme 10W-40	API: CI-4, ACEA: E4, E7	SAE: 10W-40	MAN M3277; MB-Approval 228.5; Volvo VDS-3; Mack EO-N; RENAULT VI RLD-2;	DEUTZ DQC-III-10; MTU Type 2; MTU Type 3; MAN 3275; Volvo VDS 2;	-
PLATINUM AGRO Novo 15W-40	API: CK-4/SN ACEA: E9, E7	SAE: 15W-40	MB-Approval 228.31; Volvo VDS-4.5; Renault RVI RLD-3; Mack EO-S 4.5; This product meets Cummins Eng. Std. CES20086;	Deutz DQC III- 18LA; MAN M 3775, M 3575; MTU Type 2.1; Caterpillar ECF-3; Detroit Diesel 93K222; JASO DH-2; FORD WSS-M2C171-F1; Allison TES 439;	-
PLATINUM AGRO Next 15W-40	API: CI-4/CH-4/CG-4 ACEA: E7, E5, E3	SAE: 15W-40	Volvo VDS-3; Mack EO-N; RENAULT RLD/RLD-2;	Mercedes-Benz 228.3; CUMMINS CES 20076/77/78; MTU TYPE 2; DEUTZ DQC-III-10; MAN M3275-1; CATERPILLAR ECF-2, ECF-1a;	-
PLATINUM ULTOR Basic 15W-40	API: CH-4/CG-4 ACEA: E7, E5	SAE: 15W-40	MB-Approval 228.3; DEUTZ DQC-III-10; Volvo VDS-3; Mack EO-N; RENAULT VI RLD-2;	MTU TYPE 2; Volvo VDS-2; MAN M3275-1; CATERPILLAR ECF-1a; IVECO;	-
PLATINUM AGRO Stou 10W-30	API: CG-4, GL-4 ACEA: E3	SAE: 10W-30	-	Massey Ferguson M1145, M1144, M1139; Ford M2C 159B, 159C; John Deere JDM J27; New Holland 82009201, 82009202, 82009203; ZF TE –ML 06A , 06B, 06C, 07B; CCMS D4, Sperry Vickers/Eaton: M2950S, I-286-S; Sauer Sunstrand/Danfoss: Hydrostatic Trans Fluid; AFNOR NFE68603E	-
PLATINUM AGRO Stou 10W-40	API: CG-4, GL-4 ACEA: E3	SAE: 10W-40	-	Massey Ferguson M1145, M1144, M1139; Ford M2C 159B, 159C; John Deere JDM J27; New Holland 82009201, 82009202, 82009203; ZF TE –ML 06A, 06B, 06C, 07B; CCMS D4; Sperry Vickers/Eaton: M2950S, I-286-S; Sauer Sunstrand/Danfoss: Hydrostatic Trans Fluid; AFNOR NFE68603E;	-
PLATINUM AGRO Utto 10W-30	API: GL-4 ISO HV DIN HVLP	SAE: 10W-30	-	John Deere JDM J20C, JDM J20D; Massey Ferguson CMS 1135, M1141, M1143, M1145; Allison C4; AGCO POWERFLUID 821XL; Ford ESN M2C86-B, M2C134-D; Case New Holland MAT 3540, MAT 3525, MAT 3509, MAT 3505; Case MS 1210 FNHA-2-C-200.00, FNHA-2-C-201.00; VOLVO CE WB 101 ; Caterpillar TO-2; Valtra G2-08, G2-B10; ZF TE-ML 03E, 05F, 06K, 17E, 21F; Same; Landini; Deutz-Fahr; Claas (kromě převodovky Renault); Fendt (kromě převodovky Varlo); Komatsu; Kubota UDT Fluid; Parker Denison UTTO/THF (zkoušky čerpadel T6H20C, T5D, P46); Vickers 35VQ25;	MOGUL TRAKTOL UTTO 10W-30 SUPER
PLATINUM AGRO HV 46	ISO VG 46 ISO 11158-HV		-	DIN 51524 CZ.3.	-
PLATINUM AGRO LS 80W-90	API: GL-5	SAE: 80W-90	ZF TE-ML 05, 12C, 21C (ZF001272).	MIL-L-2105D; MAN 342 M-1; Mercedes-Benz 235.0; Voith 3.325-339; Volvo 97310; Volvo 97316; Renault; ZF TE-ML 05A, 07A, 08, 16B, 16C, 16D, 16E, 17B, 19B, 21A; DAF;	-

OLEJE PRO ZEMĚDĚLSKÉ STROJE

Produkt	Kvalita	Viskozita	Atest	Splňuje kritéria	Ekvivalent MOGUL
ORLEN OIL DIESEL(2) HPDO CG-4 15W-40	API: CG-4 ACEA: E3, E2	SAE: 15W-40	-	Mercedes-Benz 228.1; MAN 271; ZETOR Proxima; Proxima Plus; Proxima Power; Forterra; Deutz DQC II-10; VDS;	MOGUL DIESEL DT
ORLEN OIL DIESEL(2) HPDO CG-4 20W-50	API: CG-4/CF ACEA: E2	SAE: 20W-50	-	Mercedes-Benz 228.1; MAN 271; MTU Type 1, ZETOR Proxima; Proxima Plus; Proxima Power; Deutz DQC I-02;	MOGUL DIESEL DT 20W-50
ORLEN OIL AGRO Stou 10W-40	API: CG-4/GL-4 ACEA: E2 ISO: HV	SAE: 10W-40	ZETOR Proxima, Proxima Plus, Proxima Power, Forterra	John Deere JDM J 27; Massey Ferguson M1139, M1144, M1145; Ford M2C 159B; Allison C-4; Caterpillar TO-2; ZF TE-ML 06B, 06C, 07B; Mercedes-Benz 227.1, 28.1, 228.3; MAN 271; MIL-L-2104D; Perkins;	-
ORLEN OIL AGRO Stou 10W-30	API: CG-4/GL-4 ACEA: E2 ISO: HV, DIN: HVLP	SAE: 10W-30	-	John Deere JDM J 27; Massey Ferguson M1139, M1144, M1145; Ford M2C 159B; Allison C-4; Caterpillar TO-2; ZF TE-ML 06B, 06C, 07B; Mercedes-Benz 227.1, 28.1, 228.3; MAN 271; MIL-L-2104D; Perkins;	MOGUL TRAKTOL STOU
ORLEN OIL AGRO Utto 10W-30	API: GL-4	SAE: 10W-30	-	Doporučeno pro použití v zemědělských strojích URUS;; Ford M2C86B,C, M2C134D; Case New Holland MAT 3525,MAT 3526; John Deere JDM J20C, J20D; Massey Ferguson CMS M1135, M1143, M1145; J.I Case MS-1204,6,7,9; Allison C-4, Volvo CE WB 101; Caterpillar TO-2; JCMAS HK P-041; Sperry Vickers/Eaton: M2950S, I-286-S; Parker (Dennison UTTO), HF -1, HF-2; Sauer Sunstrand/Danfoss: Hydrostatic Trans Fluid	MOGUL TRAKTOL UTTO 80W MOGUL TRAKTOL UTTO 10W-30
ORLEN OIL TRAWOL 2T	API: TC		-	-	-
ORLEN OIL TRAWOL 30	API: SG/CD	SAE: 30	-	-	MOGUL ALFA
ORLEN OIL TRAWOL 10W-30	API: SG/CD	SAE: 10W-30	-	-	MOGUL ALFA 4T
ORLEN OIL ALFA PROFI	ISO: VG 100		-	-	MOGUL ALFA PROFI
ORLEN OIL ALFA HOBBY	ISO: VG 100		-	-	MOGUL ALFA HOBBY

OLEJE PRO ZEMĚDĚLSKÉ STROJE

SUPEROL

Produkt	Kvalita	Viskozita	Splňuje kritéria	Ekvivalent MOGUL
ORLEN OIL SUPEROL F CD 15W-40	API: CD	SAE: 15W-40	-	-
ORLEN OIL SUPEROL CD 10W	API: CD	SAE: 10W	PN-79/C-96088/04	-
ORLEN OIL SUPEROL CD 30	API: CD	SAE: 30	-	-
ORLEN OIL SUPEROL CD 10W-30	API: CD	SAE: 10W-30	-	-
ORLEN OIL SUPEROL M CC 15W-40	API: CC	SAE: 15W-40	-	-
ORLEN OIL SUPEROL CC 30	API: CC	SAE: 30	PN-75/C-96088/03	-
ORLEN OIL SUPEROL CC 40	API: CC	SAE: 40	-	-
ORLEN OIL SUPEROL CB 30	API: CB	SAE: 30	-	MOGUL M6A
ORLEN OIL SUPEROL CB 40	API: CB	SAE: 40	-	MOGUL M9ADV
ORLEN OIL SUPEROL CB 50	API: CB	SAE: 50	-	-
ORLEN OIL SUPEROL A CB/SC 15W-40	API: CB/SC	SAE: 15W-40	-	-

PŘEVODOVÉ OLEJE

Produkt	Kvalita	Viskozita	Atest	Splňuje kritéria	Ekvivalent MOGUL
PLATINUM GEAR SX 75W-90	API: GL-5	SAE: 75W-90	-	ZF TE-ML 07A, 16B, 17B, 19B, 21A; NATO O-226;	-
PLATINUM GEAR SV 75W-80	API: GL-4	SAE: 75W-80	-	Mercedes-Benz 235.5; ZF TE-ML 02B, 08, 17A; MAN 341 Z2; DAF; Iveco; Eaton;	MOGUL SYNTRANS 75W-80
PLATINUM GEAR GL-5 80W-90	API: GL-5	SAE: 80W-90	ZF TE-ML 16B, 17B, 19B, 21A (ZF000502); ZETOR (Proxima, Forterra)	Mercedes Benz 235.0; MAN 342 typ 1; MIL-L-2105D; RENAULT; Voith 3.325-339; Volvo 97310, 97316; ZF TE-ML 07A; DAF; TATRA TDS 80/32	MOGUL TRANS 80W-90H
PLATINUM GEAR GL-4 80W-90	API: GL-4	SAE: 80W-90	ZF TE-ML 16A, 17A, 19A (ZF000500);	Mercedes Benz 235.1; MAN 341 Type Z2; MAN 341 Type E1;	-
PLATINUM GEAR GL-4 80W	API: GL-4	SAE: 80W	MB-Approval 235.1; ZF TE-ML 17A (ZF000360)	MAN 341 Type Z2; MAN 341 Type E1;	MOGUL TRANS 80
PLATINUM GEAR GL-5 85W-90	API: GL-5	SAE: 85W-90	-	MAN 342 Type M1; Mercedes Benz 235.0; MIL-L-2105D; RENAULT; Voith 3.325-339; Volvo 97310, 97316; ZF TE-ML 07A, 16B, 17B, 19B, 21A; DAF;	-
PLATINUM GEAR LS 80W-90	API: GL-5	SAE: 80W-90	ZF TE-ML 05C, 12C, 21C (ZF000603);	MIL-L-2105D; MAN 342 M-1; Mercedes-Benz 235.0; Voith 3.325-339; Volvo 97310, 97316; Renault; ZF TE-ML 07A, 08, 16B, 17B, 19B, 21A; DAF;	MOGUL TRANS LS 80W-90 H
PLATINUM GEAR LL 80W-90	API: GL-5/GL-4, MT-1	SAE: 80W-90	ZF TE-ML TE-ML 02B, 05A, 12L, 12M, 16B, 17H, 19B, 21A; MAN 342 Typ M2; MAN 341 Typ Z2;	MIL-PRF-2105E; Mercedes-Benz 235.0; SCANIA STO 1:0; RENAULT; MACK GO-J; ZF TE-ML 07A, 08; ArvinMeritor; DAF; IVECO;	MOGUL TRANS 80W-90 PLUS
PLATINUM GEAR LX 85W-140	API: GL-5	SAE: 85W-140	-	ZF TE-ML 05A, 07A, 08, 12E, 16C, 16D, 17B, 19B, 21A; Scania STO 1:0; Volvo 1273.10;	MOGUL TRANS 85W-140 PLUS
PLATINUM GEAR ATF III	Dexron III H, IIIG		-	Voith H55.6335.xx; ZF TE-ML 03D, 04D, 14A, 17C; Volvo 97341 (Volvo Std 1273.41); Volvo 97340 (Volvo Std 1273.40); MAN 339 typ Z1, typ V1; Allison C4; Ford Mercon; Mercedes-Benz 236.9;	MOGUL TRANS ATF DIII
PLATINUM GEAR DCT/DSG			-	VW (Audi, Seat, Skoda) 6-speed; VW/Audi TL 52529/ G 052 529 A2 or A6; DSG7=S-Tronic7/7 speed; VW (Audi, Seat, Skoda); VW/Audi TL 521 82, G 052 182 A2 or A6; Renault EDC 6, EDC 7, Talisman R7D; Ford/Nissan 6-speed GFT; WSS-M2C963A, 1490763/1490761; Peugeot/Citroen DCS 6-speed GFT 9734.S2; BMW Drivelogic 7-speed/ DCTF-1, 6 speed DCT; MTF LT-5; Volvo Powershift 6-speed GFT/1161838/1161839; ZF Porsche Oil #999.917.080.00; Borg Warner; Bugatti Veyron; Chryslaer 68044345 EAGGA, Powershift 6-speed, DCT-1; Ferrari 7-speed/ TE DCT-3; Mitsubishi TC-SST 6-speed GFT; MZ320065 DiaQueen SSTF-1;	-

PŘEVODOVÉ OLEJE

Produkt	Kvalita	Viskozita	Atest	Splňuje kritéria	Ekvivalent MOGUL
PLATINUM GEAR CVT			-	VW/Audi TL 521 16 (G 052 516), 521 80 (G 052 180 A2); Renault CVT CK/SK/FK; BMW Minicooper EZL 799A/83 22 0 136 376/83 22 0 429 154, 799/EZL, 799A/ZF, CVT V1; Audi Multitronic; Toyota CVFT TC, FE, GM/Saturn DEX-CVT; Hyundai/Kia CVT-1,SP III; HONDA HMMF, HCF2, Z-1 (kromě Honda Fit & Jazz rok výroby 2001-2007); Suzuki CVTF TC, 3320, 4401, NS-2, Green 162, Green 1V; Mazda JWS 3320; Volvo CVT 4959; Chery CVT; Daihatsu AMMIX CVT Fluid DFE, DC, DFC, TC; Dodge/ Jeep/ Chrysler NS-2; Dodge/Jeep/Chrysler/Mopar CVT + 4; Fiat Tutela CVT N.G; Fujijyuuko i-CVTF FG; Idemitsu CVTF-EX1; Lexus Fluid TC, FE; MG Rover EM-CVT; Mitsubishi CVTF-1, CVTF-J4/J4+, CVTF Eco J4, SP-III; Nissan KTF-1, NS-1, NS-2, NS-3, Punch CVTF-EX1; Subaru iCVT, iCVT FG, ECVT, CVT II Fluid, K0425Y0710 & K0425Y0711, HT CVT Fluid, CV-30, K0421Y0700, NS-2	-
HIPOL SEMISYNTETIC GL-5 75W-90	API: GL-5	SAE: 75W-90	-	-	MOGUL SYNTRANS 75W-90 HYP
HIPOL GL-5 85W-140	API: GL-5	SAE: 85W-140	-	-	MOGUL TRANS 85W-140H
HIPOL GL-5 80W-90	API: GL-5	SAE: 80W-90	-	-	MOGUL MOTO TRANS 80W-90
HIPOL 15F	API: GL-5	SAE: 85W-90	-	-	-
HIPOL 10F	API: GL-5	SAE: 80W	-	-	MOGUL TRANS 80H
HIPOL GL4 80W-90	API: GL-4	SAE: 80W-90	-	-	MOGUL TRANS 80W-90
HIPOL GL4 85W-140	API: GL-4	SAE: 85W-140	-	-	MOGUL TRANS 85W-140
HIPOL 6	API: GL-4	SAE: 80W	ZETOR Proxima, Proxima Plus, Forterra	-	-
HIPOL MF 80W-90	API: GL-3	SAE: 80W-90	-	-	-
HIPOL ATF II D	GM Dexron II D		MAN 339 Typ Z1, Typ V1, Typ L2; ZF TE-ML 04D, 11A, 14A; Voith H55.6335xx (G 607);	GM Dexron II D; Allison C-4;	MOGUL TRANS ATF DII
HIPOL ATF II E	GM Dexron II E		MAN 339 Typ Z2, Typ V2; ZF TE-ML 03C, 04D,14B, 17C, 20B, 25B; MB-Approval 236.9; Voith H55.6336.xx;	ZF TE-ML 14C, 16L, 16R; Allison C-4;	-
HIPOL TRANS 90H	API: GL-5		-	-	MOGUL TRANS 90H

MULTIFUNKČNÍ OLEJE

Produkt	Kvalita	Viskozita	Atest	Splňuje kritéria	Ekvivalent MOGUL
PLATINUM MULTI Utto 10W-30	API: GL-4 ISO HV, DIN HVLP	SAE: 10W-30	ZETOR (Proxima Power, Forterra Power)	John Deere JDM J20C, J20D; Massey Ferguson CMS M1135, M1141, M1143, M1145; Allison C4; White Farm (AGCO) Q-186; AGCO POWERFLUID 821XL; Ford ESN M2C86-B/C, M2C134-D; Case New Holland MAT 3540, 3525, 3509, 3505; Case MS 1210;FNHA-2-C-200.00, FNHA-2-C-201.00; Volvo CE WB 101; Caterpillar TO-2; Valtra G2-08, G2-B10; Same; Landini; Deutz-Fahr; Claas (kromě převodovky Renault); Fendt (kromě převodovky Vario); Komatsu; Kubota UDT; ZF TE-ML 03E, 05F, 06K, 17E, 21F; Parker Denison UTTO/THF (zkoušky čerpadel T6H20C, T5D, P46); Vickers 35VQ25;	-
PLATINUM MULTI Stou 10W-40	API CG-4/GL-4	SAE: 10W-40	-	Massey Ferguson M1145, M1144, M1139; Ford M2C 159B,159C; John Deere JDM J27; New Holland 82009201, 82009202, 82009203; ZF TE –ML 06A, 06B, 06C, 07B; CCMS D4; Sperry Vickers/Eaton: M2950S, I-286-S; Sauer Sunstrand/Danfoss: Hydrostatic Trans Fluid, AFNOR NFE68603E;	-
PLATINUM MULTI PTF 10W		SAE: 10W	-	Komatsu Dresser HMS B21-0006; Komatsu Micro-Clutch; Caterpillar TO-4; Alison C-4;	MOGUL HYDRO 10W
PLATINUM MULTI PTF 30		SAE: 30	-	Komatsu Dresser HMS B21-0006; Komatsu Micro-Clutch; Caterpillar TO-4; Alison C-4;	MOGUL HYDRO 30

PROVOZNÍ KAPALINY

Produkt	Splňuje kritéria
PLATINUM COOLANT Q NEW G11	ASTM D3306 BS 6580 GB 29743-2013 PN-C-40007
PLATINUM COOLANT PLUS G12	Mercedes-Benz 325.5 MAN 324 Typ Si-OAT Audi TL-774 G = G 12++ Seat TL-774 G = G 12++ Skoda TL-774 G = G 12++ Volkswagen TL-774 G = G 12++
PLATINUM COOLANT FORCE G13	Audi TL-774 J = G13 Seat TL-774 J = G13 Skoda TL-774 J = G13 Volkswagen TL-774 J = G13

SYLEN LETNÁ KVAPALINA DO OSTREKOVAČOV 5L	-
SYLEN ZIMNÁ KVAPALINA DO OSTREKOVAČOV 5L	-

PLATINUM IMPACT ROZMRAZOVAČ SKLA 0,5L	-
PLATINUM IMPACT ČISTIČ SKLA 0,5L	-
PLATINUM IMPACT ODSTRAŇOVAČ HMYZU 0,5L	-
PLATINUM IMPACT ČISTIČ KOLIES 0,5L	-

BRZDOVÁ KAPALINA DOT-3 0,5L	FMVSS 116 DOT SAE J 1703 ISO 4925 PN-C-40005:2002
BRZDOVÁ KAPALINA DOT-4 0,5L	
BRZDOVÁ KAPALINA DOT-5.1 0,5L	

ul. Opolska 114,
31-323 Kraków

www.orlenoil.pl